

NUCLEO-XXXXRX NUCLEO-XXXXRX-P

STM32 Nucleo-64 boards

Data brief

Features

- STM32 microcontroller in LQFP64 package
- External SMPS to generate Vcore logic supply (only available on '-P' suffixed boards)
- 1 user LED shared with Arduino™
- 1 user and 1 reset push-buttons
- 32.768 kHz LSE crystal oscillator
- Board expansion connectors:
 - Arduino[™] Uno V3
 - ST morpho extension pin headers for full access to all STM32 I/Os
 - External SMPS experimentation dedicated connector (only available on '-P' suffixed boards)
- Flexible power-supply options: ST-LINK USB V_{BUS} or external sources
- On-board ST-LINK/V2-1 debugger/programmer with USB reenumeration capability. Three different interfaces supported on USB: mass storage, Virtual COM port and debug port


- Comprehensive free software libraries and examples available with the STM32Cube MCU Package
- Support of a wide choice of Integrated Development Environments (IDEs) including IAR[™], Keil[®], GCC-based IDEs, Arm[®] Mbed[™]
- Arm[®] Mbed Enabled[™] compliant (only for some Nucleo part numbers)

Table 1. Device summary

Reference	Part number
NUCLEO-XXXXRX (-P)	NUCLEO-F030R8, NUCLEO-F070RB, NUCLEO-F072RB, NUCLEO-F091RC, NUCLEO-F103RB, NUCLEO-F302R8, NUCLEO-F303RE, NUCLEO-F334R8, NUCLEO-F401RE, NUCLEO-F410RB, NUCLEO-F411RE, NUCLEO-F446RE, NUCLEO-L010RB, NUCLEO-L053R8, NUCLEO-L073RZ, NUCLEO-L152RE, NUCLEO-L452RE, NUCLEO-L476RG, NUCLEO-L412RB-P, NUCLEO-L452RE-P, NUCLEO-L433RC-P.







Top view of a NUCLEO-XXXXRX-P board with SMPS.

Pictures are not contractual.



Description

The STM32 Nucleo-64 boards provide an affordable and flexible way for users to try out new concepts and build prototypes with the STM32 microcontrollers, choosing from various combinations of performance, power consumption and features. For the compatible boards, the SMPS significantly reduces power consumption in Run mode.

The Arduino[™] Uno V3 connectivity support and the ST morpho headers allow the easy expansion of the functionality of the STM32 Nucleo open development platform with a wide choice of specialized shields.

The STM32 Nucleo-64 board does not require any separate probe as it integrates the ST-LINK/V2-1 debugger and programmer.

The STM32 Nucleo-64 board comes with the STM32 comprehensive software HAL library together with various packaged software examples, as well as direct access to the Arm[®] Mbed^{™(a)} online resources at http://mbed.org.

System requirement

- Windows[®] OS (7, 8 and 10), Linux[®] 64-bit or macOS^{®(b)}
- USB Type-A to Mini-B cable or USB Type-A to Micro-B cable

Development toolchains

- Keil[®]: MDK-ARM^(c)
- IAR[™]: EWARM^(c)
- GCC-based IDEs including free SW4STM32 from AC6
- Arm[®] Mbed[™] online^(d) (see http://mbed.org)

2/6 DB2196 Rev 11

a. Arm and Mbed are registered trademarks or trademarks of Arm Limited (or its subsidiaries) in the US and or elsewhere.

b. macOS® is a trademark of Apple Inc.\nregistered in the U.S. and other countries.

c. On Windows® only

d. Refer to the https://www.mbed.com website and to *Table 2: Ordering information*, to determine which Nucleo board order codes are supported.

Demonstration software

The demonstration software, included in the STM32Cube MCU Package, is preloaded in the STM32 Flash memory for easy demonstration of the device peripherals in standalone mode. The latest versions of the demonstration source code and associated documentation can be downloaded from the www.st.com/stm32nucleo website.

Ordering information

To order the STM32 Nucleo-64 board, refer to Table 2.

Table 2. Ordering information

Order code	Targeted STM32
NUCLEO-F030R8 ⁽¹⁾	STM32F030R8T6
NUCLEO-F070RB ⁽¹⁾	STM32F070RBT6
NUCLEO-F072RB ⁽¹⁾	STM32F072RBT6
NUCLEO-F091RC ⁽¹⁾	STM32F091RCT6
NUCLEO-F103RB ⁽¹⁾	STM32F103RBT6
NUCLEO-F302R8 ⁽¹⁾	STM32F302R8T6
NUCLEO-F303RE ⁽¹⁾	STM32F303RET6
NUCLEO-F334R8 ⁽¹⁾	STM32F334R8T6
NUCLEO-F401RE ⁽¹⁾	STM32F401RET6
NUCLEO-F410RB ⁽¹⁾	STM32F410RBT6
NUCLEO-F411RE ⁽¹⁾	STM32F411RET6
NUCLEO-F446RE ⁽¹⁾	STM32F446RET6
NUCLEO-L010RB ⁽¹⁾	STM32L010RBT6
NUCLEO-L053R8 ⁽¹⁾	STM32L053R8T6
NUCLEO-L073RZ ⁽¹⁾	STM32L073RZT6
NUCLEO-L152RE ⁽¹⁾	STM32L152RET6
NUCLEO-L452RE	STM32L452RET6
NUCLEO-L476RG ⁽¹⁾	STM32L476RGT6
NUCLEO-L412RB-P	STM32L412RBT6P
NUCLEO-L433RC-P	STM32L433RCT6P
NUCLEO-L452RE-P	STM32L452RET6P

^{1.} Arm[®] Mbed Enabled™.



DB2196 Rev 11 3/6

The meaning of the codification is explained in *Table 3*.

Table 3. Codification explanation

NUCLEO-TXXXRY-P	Description	Example: NUCLEO-L452RE
TXXX	STM32 product line	STM32L452
R	STM32 package pin count 64 pins	
Υ	STM32 Flash memory size: - 8 for 64 Kbytes - B for 128 Kbytes - C for 256 Kbytes - E for 512 Kbytes - G for 1 Mbyte - Z for 192 Kbytes	512 Kbytes
P = SMPS	MCU has SMPS function	-

The order code is printed on a sticker placed at the top or bottom side of the board.

Revision history

Table 4. Document revision history

Date	Revision	Changes
10-Feb-2014	1	Initial release.
13-Feb-2014	2	Added Table 1: Device summary and updated Table 2: Ordering information.
11-Apr-2014	3	Extended the applicability to NUCLEO-F302R8. Updated Table 1: Device summary and Table 2: Ordering information.
26-May-2014	4	Extended the applicability to NUCLEO-L053R8, NUCLEO-F072RB, NUCLEO-F334R8 and NUCLEO-F411RE
		Updated Table 1 and Table 2.
09-Sep-2014	5	Extended the applicability to NUCLEO-F091RC and NUCLEO-F303RE. Updated Features. Updated Table 1: Device summary and Table 2: Ordering information.
16-Dec-2014	6	Extended the applicability to NUCLEO-F070RB, NUCLEO-L073RZ and NUCLEO-L476RG. Updated Table 1: Device summary and Table 2: Ordering information.
08-Jul-2015	7	Extended the applicability to NUCLEO-F410RB, NUCLEO-F446RE. Updated <i>Table 1: Device summary</i> and <i>Table 2: Ordering information</i> .
29-Nov-2016	8	Extended the applicability to NUCLEO-L452RE. Updated <i>Table 1: Device summary</i> and <i>Table 2: Ordering information</i> . Added <i>Table 3: Codification explanation</i> .
16-Nov-2017	9	Extended document scope to the NUCLEO-L452RE-P and NUCLEO-L433RC-P boards: - Updated Features - Updated Table 1: Device summary, Table 2: Ordering information and Table 3: Codification explanation - Updated System requirement, Development toolchains and Demonstration software
15-Dec-2017	10	Updated Features, Description and System requirement. Extended document scope to the NUCLEO-L010RB board: updated Table 1: Device summary and Table 2: Ordering information.
24-Aug-2018	11	Extended document scope to the NUCLEO-L412RB-P board: updated <i>Table 1: Device summary</i> and <i>Table 2: Ordering information</i> .



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics - All rights reserved

6/6 DB2196 Rev 11

