

Product Specification

Product class: COB Cover Plate

ItemNo.:DK-48-GB-K-G

Material: PC

Certification: RoHS


Set Up:PeiShanWu

Check:XiaoHuiLiang


Content

Specification-----	3
2D Drawing-----	4
Packing Details-----	5
Application Notes-----	6

Specification

Item No	Picture	Size	Lighting Application
DK-48-GB-K-G		Diameter: $\Phi 47.8\text{mm}$ Height: 1.2mm	Reflector - K Series

Drawing



Packing Details

Packing Material	Packing Materil size	Packing Specification
Pearl wool	315*230mm	1400pcs/Inner box 4 Inner box / 1 outer box
Plastic Bag	170*300mm	
Protective Film	40mm	
White paperboard	A level; 400g; 310*235mm	
Inner box	335*245*105mm	
Outer box	A=B 510*330*255mm	

Application Notes

- (1) Please use a little water and soft fabric (air-laid paper) to clean the product if necessary.
- (2) Forbid to use industrial solvent to clean the product, such as alcohol.
- (3) The working temperature is $-40^{\circ}\text{C}\sim+80^{\circ}\text{C}$ (PMMA) or $-35^{\circ}\text{C}\sim+120^{\circ}\text{C}$ (PC).
- (4) Storage environment temperature is $0^{\circ}\text{C}\sim40^{\circ}\text{C}$, humidity is 30%~95%.
- (5) The product has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- (6) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- (7) Please wear gloves once install the product, avoid to abrasion the product surface.
- (8) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.